



■ Specifications :

- Voltage rating: 125V AC / DC
- Current rating: 1.0A AC / DC
- Withstanding voltage: 500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥100MΩ
- Contact resistance: ≤20mΩ
- After environmental testing: ≤40mΩ

0125 W V A-2x03 - N0 B P 37 B R 001 F

(11) (12) (13) (14) (15) (16) (17) (18) (19) (20) (21) (22) (23)

- (01) Series No.
- (02) Category: W-wafer
- (03) Connector type: V-Straight 180°
- (04) Mounting type: A-Male Housing
- (05) Row No.-Pin No per row: 2x03-Single Row 2x03Pin
- (06) Plastic material: N0- PA66 94V-0;
- (07) Color: B-Black;
- (08) Metal material: P-Phosphor bronze
- (09) Plating Code: 37- nickel base at all area Min 50 u", bright tin Min 100 u", gold-plated at contact region Min 3 u".
- (10) Packag: B-bags
- (11) Green code: R-RoHS
- (12) Water code: 001 Special code:
- (13) F----Other Connectors

DATE	OLD REV	NEW REV	ECN	DESCRIPTION	CHECK	APPROVAL

GENERAL TOLERANCE	
.X	±0.30
.XX	±0.20
.XXX	±0.10
PROJECT	

东莞市思量连接器有限公司 DONGGUAN ADZL CONNECTORS CO.,LTD.			
APPROVAL	CHECK	DRAWN	DATA
Ken	Zhao Hong	Allen	2018/08/31

PART NO.			
0125MVA-2*03-N0BP37BR001F			
TITLE			
1.25mm Crimp Style Connectors			
UNIT	SCALE	NUMBER	REV
MM	1:1		