



Specifications :

- Voltage rating: 100V AC / DC
- Current rating: 2.0A AC / DC
- Withstanding voltage: 800V AC/minute
- Temperature range: -50°C~+150°C
- Insulation resistance: ≥1000MΩ
- Contact resistance: ≤10mΩ
- After environmental testing: ≤20mΩ
- Material(Pin): Brass
- Material( Solder Tab): Brass

2013 W R S-XX XX - LP SN XX R  
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

- ① Series No.
- ② Category: W-WAFER
- ③ Welding Board Angle: R-Right Angle 90°
- ④ Welding Way: S-SMT
- ⑤ Row No.-Pin No.: XX-02P~05P
- ⑥ Plug the Pin & Special No.: D-Terminal body
- ⑦ Material: LP -LCP UL 94V-0
- ⑧ Plating Category: SN-Bright Tin Plating
- ⑨ Color : Blank-Natural Color
- ⑩ Packag: R-Reel

Poles	Dimensions (mm)			
	A	B	C	D
02	2.00	7.90	4.80	6.50
03	4.00	9.90	6.80	8.50
04	6.00	11.90	8.80	10.50
05	8.00	13.90	10.80	12.50

							GENERAL TOLERANCE .X ±0.30 .XX ±0.20 .XXX ±0.10				PART NO. 2013WRS-XX-LPSNR			
							APPROVAL    CHECK    DRAWN    DATA				TITLE 2.00mm Crimp Style Connectors			
DATE	OLD REV	NEW REV	ECN	DESCRIPTION	CHECK	APPROVAL	Ken	Zhao Hong	Allen	2022/03/02	UNIT MM	SCALE 1:1	NUMBER	REV

